

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) A radio communication system comprising a network structure which arranges a plurality of node devices each having a radio unit and performs radio communications of the respective node devices with their neighboring node devices to realize the communications among the respective node devices, and a management device for managing the network via at least one of the node devices, wherein:

the node device comprises:

a GPS device for inputting GPS information which is sent from a GPS satellite and received by a GPS antenna;

transmission means for sending position information generated by the GPS device to the management device; and

control means for receiving a control signal generated by the management device according to the position information sent from the transmission means and controlling respective sections of the radio unit according to the control signal; and

the management device comprises:

control signal generation means which receives the position information from the node device and generates the control signal for controlling respective sections of the node device that sent the position information, according to the position information; and

control signal transmission means which sends the generated control signal to a pertinent node device.

2. (Currently amended) The radio communication system according to claim 1, wherein:

the radio unit ~~is configured of~~ comprises an outdoor device disposed outdoors and an indoor device disposed indoors and connected to the outdoor device through a coaxial cable;

the GPS antenna is installed outdoors; and

the GPS information received by the GPS antenna is input to the GPS device via the outdoor device, the coaxial cable and the indoor device.

3. (Original) The radio communication device according to claim 2, wherein:
the outdoor device comprises multiple separation means which superimposes the GPS information received by the GPS antenna on a communication signal to an adjacent node device and sends to the coaxial cable; and

the indoor device comprises multiple separation means which separates the GPS information from the signal being sent through the coaxial cable and inputs to the GPS device.

4. (Original) The radio communication system according to claim 1, wherein the GPS antenna is installed indoors and the GPS information received by the PGS antenna is directly input to the GPS device.

5. (Original) The radio communication system according to claim 1, wherein the node device comprises clock generating means which receives a synchronization signal generated by the GPS device from time information which is contained in the GPS information and generates an internal operation clock of the own device according to the synchronization signal.

6. (Original) The radio communication device according to claim 5, wherein:
the node device comprises means for generating a self clock and means for extracting a clock from a radio communication channel in an associated section to take it as a line clock; and
the clock generation means comprises means for selecting one of the internal operation clock generated from the time information, the self clock and the line clock.

7. (Original) The radio communication system according to claim 1, wherein:
the control signal generation means comprises:

arithmetic means for calculating a direction of the antenna according to the
position information received from each node device so that centers of antennas of the
respective radio units of both of the mutually neighboring node devices are faced to each
other; and

antenna direction adjusting control signal generation means for generating an
antenna direction adjusting control signal for adjusting the antennas of the respective
radio units of both of the node devices to direct them in the calculated antenna direction;
and the control means comprises:

antenna direction adjustment means for adjusting the direction of the antenna of
the radio unit of the own node device according to the antenna direction adjusting control
signal received from the management device.

8. (Original) The radio communication system according to claim 7, wherein:
the radio unit has azimuthal direction rotating means and elevational direction rotating
means which respectively rotate the antenna in an azimuthal direction and an elevational
direction; and

the antenna direction adjustment means comprises means for driving the azimuthal
direction rotating means and the elevational direction rotating means to respectively rotate the
antenna in the azimuthal direction and the elevational direction according to the antenna
direction adjusting control signal.

9. (Original) The radio communication system according to claim 1, wherein:
the control signal generation means comprises:

radio level arithmetic means which calculates an optimum radio level of each
radio unit of neighboring node devices corresponding to a distance between the
neighboring node devices according to the position information received from the
respective node devices; and

radio level adjusting control signal generation means which generates a radio
level adjusting control signal for adjusting radio levels of the radio units of the
neighboring node devices to the calculated radio levels respectively; and

the control means comprises radio level adjustment means which adjusts the radio level
of the radio unit of the own node device according to the radio level adjusting control signal
received from the management device.

10. (Original) The radio communication system according to claim 9, wherein the
radio level is at least either one of the transmission level and the reception level.

11. (Original) The radio communication system according to claim 1, wherein the
management device comprises:

a map database which stores electronic map data on an installation area of the node
devices; and

display control means which displays node icons of the pertinent node devices at the
pertinent positions on the electronic map according to the position information received from the
node devices.

12. (Original) The radio communication system according to claim 11, wherein:
the node device comprises means for sending node identification information about the own device to the management device; and
the management device comprises means for displaying the node identification information together with node icons corresponding to the node devices according to the node identification information received from the node devices.

13. (Original) The radio communication system according to claim 11 or 12, wherein:
the node device comprises:
connection recognition means which recognizes a connected relation between the own node and an adjacent node device; and
connected state information transmission means which sends connected state information showing the recognized connected relation to the management device; and
the management device comprises:
connection management means which manages normal connected relation information between node devices being managed;
judging means which compares the connected state information received from the respective node devices and the connected state information managed by the connection management means and judges connected states between the respective node devices; and
connected state drawing means which draws lines indicating the connected states of the respective node devices between node icons corresponding to the respective node devices according to the judged result obtained by the judging means.

14. (Original) The radio communication system according to claim 13, further comprising means for alarming a mis-connected state when the judging means judges that the respective node devices are in the mis-connected state.

15. (Original) The radio communication system according to claim 1, wherein the node device is an ATM communication device for communicating by an asynchronous transfer mode (ATM) transmission system, and the entire network is configured by an ATM network.

16-19. (Canceled)

20. (Original) A radio communication system comprising a network structure which arranges a plurality of node devices each having a radio unit and performs radio communications of the respective node devices with their neighboring node devices to realize the communications among the respective node devices, and a management device for managing the network via at least one of the node devices, wherein:

the node device comprises:

a GPS device which inputs GPS information received from a GPS satellite;

transmission means which sends position information generated by the GPS device to the management device; and

antenna direction adjusting means which adjusts a direction of the antenna of the radio unit of the own node device according to antenna direction adjusting control signal generated by the management device according to the position information; and

the management device comprises:

arithmetic means which calculates directions of the antennas according to the position information received from the respective node devices so that centers of the antennas of the respective radio units of both of the mutually neighboring node devices are faced to each other;

antenna direction adjusting control signal generation means which generates the antenna direction adjusting control signal for adjusting the antennas of the respective radio units of both of the node devices to face them in the calculated antenna direction; and

control signal transmission means which sends the generated antenna direction adjusting control signal to the pertinent node devices.

21. (Original) The radio communication system according to claim 20, wherein:
- the radio unit has azimuthal direction rotating means and elevational direction rotating means which respectively rotate the antenna in an azimuthal direction and an elevational direction; and
- the antenna direction adjustment means comprises means for driving the azimuthal direction rotating means and the elevational direction rotating means to respectively rotate the antenna in the azimuthal direction and the elevational direction according to the antenna direction adjusting control signal.

22. (Original) A radio communication system comprising a network structure which arranges a plurality of node devices each having a radio unit and performs radio communications of the respective node devices with their neighboring node devices to realize the communications among the respective node devices, and a management device for managing the network via at least one of the node devices, wherein:

the node device comprises:

a GPS device which inputs GPS information received from a GPS satellite;

transmission means which sends position information generated by the GPS device to the management device; and

radio level adjusting means which adjusts a radio level of the radio unit of the own node device according to a radio level adjusting control signal generated by the management device according to the position information; and

the management means comprises:

radio level arithmetic means which calculates an optimum radio level of the respective radio units of both of the node devices corresponding to a distance between both of the node devices according to the position information received from the respective node devices;

radio level adjusting control signal generation means which generates the radio level adjusting control signal for adjusting the radio levels of the radio units of both of the node devices to the calculated radio level respectively; and

control signal transmission means which sends the generated antenna direction adjusting control signal to the pertinent node devices.

23. (Original) The radio communication system according to claim 22, wherein the radio level is at least either one of the transmission level and the reception level.

24. (Canceled)

25. (Canceled)

26. (Original) A radio communication system comprising a network structure which arranges a plurality of node devices each having a radio unit and performs radio communications of the respective node devices with their neighboring node devices to realize the communications among the respective node devices, and a management device for managing the network via at least one of the node devices, wherein:

the node device comprises:

a GPS device which inputs GPS information received from a GPS satellite;

connection recognition means which recognizes a connected relation between the own node and the adjacent node devices;

transmission means which transmits position information generated by the GPS device and connected state information showing a connected relation recognized by the connection recognition means to the management device;

the management device comprises:

a map database which stores electronic map data about an installation area of the node devices;

display control means which displays node icons of the pertinent node devices at the pertinent positions on the electronic map according to the position information received from the node devices;

connection management means which manages normal connected relation information between the node devices being managed;

judging means which compares the connected state information received from the respective node devices and the connected state information managed by the connection management means and judges connected states between the respective node devices; and

connected state drawing means which draws lines indicating the connected states of the respective node devices between the node icons corresponding to the respective node devices according to the judged result obtained by the judgment means.

27. (Original) The radio communication system according to claim 26, wherein:
the node device further comprises means for transmitting node identification information about the own device to the management device; and
the management device comprises means for displaying the node identification information together with the node icons corresponding to the pertinent node devices according to the node identification information received from the node devices.

28. (Original) The radio communication system according to claim 26 or 27, further comprising means for alarming a mis-connected state when the judging means judges that the respective node devices are in the mis-connected state.